

Steady State Radial Flow Pressure Diffusion @model

Motivation

In many practical cases the [Radial Flow Pressure Diffusion](#) is evolving towards pressure [stabilization](#) and can be efficiently analyzed using the [steady state flow model](#).

Inputs & Outputs

Inputs		Outputs	
q_i	total sandface rate	$p(r)$	reservoir pressure
p_i	initial formation pressure	p_{wf}	well bottomhole pressure
σ	transmissibility, $\sigma = \frac{k\,h}{\mu}$		
S	skin-factor		
r_w	wellbore radius		
r_e	drainage radius		

k	absolute permeability
h	effective thickness
μ	dynamic fluid viscosity
ϕ	porosity

Physical Model

Radial fluid flow	Homogenous reservoir	Finite reservoir flow boundary	Slightly compressible fluid flow	Constant rate	Constant skin
$p(t, \mathbf{r}) \rightarrow p(r)$ $\mathbf{r} \in \mathbb{R}^2 = \{x, y\}$	$M(r, p) = M = \text{const}$ $\phi(r, p) = \phi = \text{const}$ $h(r) = h = \text{const}$ $c_r(r) = c_r = \text{const}$	$r_w \leq r \leq r_e < \infty$	$c_t(r, p) = \text{const}$	$q_i = \text{const}$	$S =$

Mathematical Model

(1) $r_{wf} < r \leq r_e$	(3) $\frac{\partial^2 p}{\partial r^2} + \frac{1}{r} \frac{\partial p}{\partial r} = 0$	(4) $p(r_e) = p_i$	(5) $\left[r \frac{\partial p(r)}{\partial r} \right]_{r \rightarrow r_w} = \frac{q_t}{2\pi\sigma}$
(2) $p(t, r) = p(r) \Leftrightarrow \frac{\partial p}{\partial t} = 0$			
(6) $p_{wf} = p(r_w) - S \cdot r_w \left. \frac{\partial p}{\partial r} \right _{r=r_w}$			
(7) $p(r) = p_i + \frac{q_t}{2\pi\sigma} \ln \frac{r}{r_e} = p(r_w) + \frac{q_t}{2\pi\sigma} \ln \frac{r}{r_w}, \quad r_{wf} < r \leq r_e$		(8) $p_{wf} = p_i - \frac{q_t}{2\pi\sigma} \left[S + \ln \frac{r_e}{r_w} \right]$	

Applications

Equation (7) shows how the [basic diffusion model parameters](#) impact the relation between [drawdown](#) $\Delta p = p_i - p_{wf}$ and [total sandface flowrate](#) q_t and plays important methodological role as they are used in many algorithms and express-methods of [Pressure Testing](#).

The [Total Sandface Productivity Index](#) for low-compressibility fluid and low-compressibility rocks does not depend on [formation pressure](#), [bottomhole pressure](#) and the [flowrate](#) and can be expressed as:

$$(9) \quad J_t = \frac{q_t}{p_i - p_{wf}(t)} = \frac{2\pi\sigma}{\ln \frac{r_e}{r_w} + S} = \text{const}$$

The [Field-average Productivity Index](#) for low-compressibility fluid and low-compressibility rocks does not depend on [formation pressure](#), [bottomhole pressure](#) and the [flowrate](#) and can be expressed as:

$$(10) \quad J_t = \frac{q_t}{p_r(t) - p_{wf}(t)} = \frac{2\pi\sigma}{\ln \frac{r_e}{r_w} + 0.5 + S} = \text{const}$$

See Also

[Physics](#) / [Mechanics](#) / [Continuum mechanics](#) / [Fluid Mechanics](#) / [Fluid Dynamics](#) / [Radial fluid flow](#) / [Pressure diffusion](#) / [Pressure Diffusion @model](#) / [Radial Flow Pressure Diffusion @model](#)

[Petroleum Industry](#) / [Upstream](#) / [Subsurface E&P Disciplines](#) / [Well Testing](#) / [Pressure Testing](#)

[[Well & Reservoir Surveillance](#)]

