

STOIP @model

@wikipedia

Volumetric value of Oil Initial In Place (OIIP) recalculated to NTP conditions:

$$(1) \quad V_{\text{STOIP}} = \int_{\Omega} \left[\frac{s_{oi}(\mathbf{r})}{B_o} + \frac{R_v s_{gi}(\mathbf{r})}{B_g} \right] \phi_e(\mathbf{r}) dV$$

where

Ω	Petroleum reservoir
$\mathbf{r} = (x, y, z)$	Position vector to some location in a reservoir
$dV = dx dy dz$	Volume element of a reservoir
$p_i(\mathbf{r}), T_i(\mathbf{r})$	Initial formation pressure and temperature at location \mathbf{r}
$\phi_e(\mathbf{r})$	Effective porosity at location \mathbf{r}
$s_{oi}(\mathbf{r}), s_{gi}(\mathbf{r})$	Initial Oil saturation and Gas saturation at location \mathbf{r}
$B_o(p_i, T_i), B_g(p_i, T_i)$	Oil FVF and Gas FVF at Initial formation pressure and temperature
$R_s(p_i, T_i), R_v(p_i, T_i)$	Solution GOR and Vaporized Oil Ratio at Initial formation pressure and temperature

For practical implementation of (1) one needs to build a Geological Model (GM) and perform a numerical integration.

See Also

[Petroleum Industry](#) / [Upstream](#) / [Exploration](#) / [Booking Reserves](#) / [Oil Initial In Place \(OIIP\)](#) / [Stock-Tank Oil Initial In-Place \(STOIP\)](#)