

Derivation of pseudo-linear pressure diffusion @model

We start with reservoir pressure diffusion outside wellbore:

$(1) \quad \frac{\partial(\rho\phi)}{\partial t} + \nabla(\rho \mathbf{u}) = 0$	$(2) \quad \int_{\Sigma_k} \mathbf{u} d\mathbf{A} = q_k(t)$
---	---

where

Σ_k	well-reservoir contact of the k -th well
$d\mathbf{\Sigma}$	normal vector of differential area on the well-reservoir contact, pointing inside wellbore

Then use the following equality:

$$(3) \quad d(\rho\phi) = \rho d\phi + \phi d\rho = \rho\phi \left(\frac{d\phi}{\phi} + \frac{d\rho}{\rho} \right) = \rho\phi \left(\frac{1}{\phi} \frac{d\phi}{dp} dp + \frac{1}{\rho} \frac{d\rho}{dp} dp \right) = \rho\phi (c_\phi dp + c dp) = \rho\phi c_t dp$$

to arrive at:

$(4) \quad \rho\phi c_t \cdot \frac{\partial p}{\partial t} + \nabla(\rho \mathbf{u}) = 0$	$(5) \quad \int_{\Sigma_k} \mathbf{u} d\mathbf{A} = q_k(t)$
--	---

where

$c_t = c_\phi + c$	total compressibility
--------------------	-----------------------

Let's assume Darcy flow with constant permeability $\frac{dk}{dp} = 0$ and ignore gravity forces:

$$(6) \quad \mathbf{u} = \frac{k}{\mu} \nabla p$$

so that diffusion equation becomes:

$(7) \quad \rho\phi c_t \cdot \frac{\partial p}{\partial t} + \nabla \left(k \cdot \frac{\rho}{\mu} \nabla p \right) = 0$	$(8) \quad \frac{k}{\mu} \cdot \int_{\Sigma_k} \nabla p \cdot d\mathbf{A} = q_k(t)$
--	---

Let's express the density via Z-factor:

$$(9) \quad \rho = \frac{M}{RT} \frac{p}{Z(p)}$$

where

T	fluid temperature
M	molar mass of a fluid
R	gas constant

and assuming the fluid temperature T does not change over time and space during the modelling period:

$$(10) \quad \phi c_t \mu \cdot \frac{p}{\mu Z} \cdot \frac{\partial p}{\partial t} + \nabla \left(k \cdot \frac{p}{\mu Z} \nabla p \right) = 0$$

$$(11) \quad \frac{k}{\mu} \cdot \int_{\Sigma_k} \nabla p \cdot d\mathbf{A} = q_k(t)$$

or

$$(12) \quad \phi c_t \mu \cdot \frac{\partial \Psi}{\partial t} + \nabla (k \cdot \nabla \Psi) = 0$$

$$(13) \quad \frac{k}{\mu} \cdot \int_{\Sigma_k} \nabla p \cdot d\mathbf{A} = q_k(t)$$

where

$$\Psi(p) = 2 \int_0^p \frac{p \, dp}{\mu(p) Z(p)}$$

Pseudo-Pressure

In some practical cases the complex $c_t \mu$ can be considered as constant in time which makes (12) a linear differential equation.

But during the early transition times the pressure drop is usually high and the complex $c_t \mu$ can not be considered as constant in time which leads to distortion of [pressure transient diagnostics](#) at early times.

In this case one can use [Pseudo-Time](#), calculated by means of the [bottom-hole pressure](#) $p_{BHP}(t)$:

$$(14) \quad \tau(t) = \int_0^t \frac{dt}{\mu(p_{BHP}) c_t(p_{BHP})}, \quad p_{BHP} = p_{BHP}(t)$$

to correct [early-time transient](#) behaviour which turn equation (12) into:

$$(15) \quad \phi \cdot \frac{\partial \Psi}{\partial \tau} + \nabla (k \cdot \nabla \Psi) = 0$$

See also

[Physics](#) / [Mechanics](#) / [Continuum mechanics](#) / [Fluid Mechanics](#) / [Fluid Dynamics](#) / [Pressure Diffusion](#) / [Pressure Diffusion @model](#) / [Pseudo-linear pressure diffusion @model](#)