

# Fluid Capacitance Log = FCAP

@wikipedia

Fluid Capacitance record [along the borehole](#) normalized by [Fluid Capacitance](#) of distilled water at the same temperature [along the borehole](#)  $T(l)$ .

$$(1) \quad Y_f(l) = \frac{\epsilon_f(l)}{\epsilon_w^*(T(l))}$$

where  $\epsilon_w^*$  is [Fluid Capacitance](#) for distilled water at temperature  $T(l)$ .

<b>Log Name</b>	FCAP		
<b>Math Symbol</b>	$Y_f$		
<b>Logging Tool</b>	<a href="#">Fluid Capacitance Logging Tool</a>		
<b>Model</b>	<a href="#">Fluid Capacitance @model</a>		
<b>Units</b>	<b>SI</b>	<b>Oil Metric</b>	<b>Oil Field</b>
	%	%	%

Typical values of [FCAP](#) for petroleum fluids at [SPE STP](#) are:

Water	Oil	Gas
100%	25%	7%

## See Also

---

[Petroleum Industry](#) / [Upstream](#) / [Data Acquisition](#) / [Well & Reservoir Surveillance](#) / [Well logging](#) / [Cased-Hole Logging](#) / [Production Logging \(PLT\)](#) / [Borehole Flow Profile \(BFP\)](#)

[Subsurface E&P Disciplines](#) / [Fluid Analysis](#) / [Fluid Capacitance](#)