

Pressure Control (Reservoir Flow Modelling)

Specification of [DFM](#) dynamic inputs and outputs at [well](#) level:

Dynamic Input	Dynamic Output
• BHP	• Liquid rate • Formation pressure • Water cut • GOR

The [pressure control](#) is a usual condition for [water injectors](#) and [gas injectors](#) and specified by the [THP](#) maintained by the ground booster pump.

In this case a reservoir takes as much fluid as it can depending on quality of [well-reservoir contact](#) and [reservoir capacity](#) and [reservoir transmissibility](#) around a given [injector](#).

Sometimes [producing wells](#) produce at nearly constant [bottomhole pressure](#), when it is being reduced by the downhole pump to its minimal value $p_{wf} = p_{wf,min} = \text{const}$, specified by the pump location inside the [wellbore](#).

In this case the liquid rate is declining $q_L^\uparrow(t) < q_{LL}^\uparrow$

This does not actually qualifies this production as [Pressure Control](#) and the well is still under [Liquid Control](#) conditions and once [bottomhole pressure](#) raises above minimal the pump returns to producing the target liquid rate $q_L^\uparrow(t) = q_{LL}^\uparrow = \text{const}$.

See also

[Petroleum Industry / Upstream / Subsurface E&P Disciplines / Dynamic Flow Modelling / Reservoir Flow Modelling / Well Control \(Reservoir Flow Modelling\)](#)

[Petroleum Industry / Upstream / Production / Subsurface Production Operations / Well Control / Pressure Control](#)